## **Amendment to the Abstract:**

The Abstract has been amended. A revised Abstract is attached.

## **ABSTRACT**

The present invention comprises A portable receiver includes an antenna 21 to which at least FM broadcast wave is inputted, a matching circuit 23 to which the signal input to the antenna 21 is supplied via minute resistance component, an FM receiver unit 24 with the output of the matching circuit 23 connected thereto, and an earphone 25 connected to the output of the FM receiver unit 24, wherein the . The antenna 21 is formed from rigid metal, and its length is shorter than the quarter wavelength of the FM broadcast wave, and the. The matching circuit 23 is formed by reactance element having fine DC resistance, and the. The impedance value of the resistance component as viewed via the resistance component from the matching circuit 23 is nearly equal to the impedance of the matching circuit—23.

Respectfully submitted,

Lawrence E. Ashery, Reg. No. 34,515

Attorney for Applicants

Attachment: Abstract

Dated: April 13, 2004

P.O. Box 980 Valley Forge, PA 19482 (610) 407-0700

The Commissioner for Patents is hereby authorized to charge payment to Deposit Account No. **18-0350** of any fees associated with this communication.

EXPRESS MAIL: Mailing Label Number: EV 418 253 227 US
Date of Deposit: April 13, 2004

I hereby certify that this paper and fee are being deposited, under 37 C.F.R. § 1.10 and with sufficient postage, using the "Express Mail Post Office to Addressee" service of the United States Postal Service on the date indicated above and that the deposit is addressed to the Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.

KATHLEEN LIBBY

Page 2 of 3

## **ABSTRACT**

A portable receiver includes an antenna to which at least FM broadcast wave is inputted, a matching circuit to which the signal input to the antenna is supplied via minute resistance component, an FM receiver unit with the output of the matching circuit connected thereto, and an earphone connected to the output of the FM receiver unit. The antenna is formed from rigid metal, and its length is shorter than the quarter wavelength of the FM broadcast wave. The matching circuit is formed by reactance element having fine DC resistance. The impedance value of the resistance component as viewed via the resistance component from the matching circuit is nearly equal to the impedance of the matching circuit.